

MEN'S S-WORKS TURBO LEVO FSR 6FATTIE/29



CARB/HYP

If it wasn't for the faint glimpse of green LEDs flashing through the forest as you send it down through the trees, you'd surely forget that you were riding an e-MTB, which is exactly what makes the S-Works Turbo Levo FSR 6Fattie/29 so much different than all the others. It's a trail bike, just with a little extra oomph.

- The S-Works Turbo Levo FSR frame is constructed entirely of FACT 11m carbon fiber, making it not only lightweight but also remarkably stiff and responsive. The design includes our Trail 6Fattie Geometry that includes a low bottom bracket, roomy top tube, and short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-504 battery features an integrated Trail Display and ANT+/Bluetooth® module with Mission Control App connectivity. It also houses 504Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	554	581	611	644
BB Drop (mm)	18	18	18	18
BB Height (mm)	340	340	340	340
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	69	69	69	69
Seat Tube Angle - Effective (deg)	74.2	73.9	73.6	73.3
Head Tube Angle (deg)	66.1	66.1	66.1	66.1
Wheelbase (mm)	1157	1185	1215	1250
Standover Height (mm)	753	762	772	780
Head Tube Length (mm)	95	100	130	150
Stack (mm)	598	603	630	649
Reach (mm)	386	411	430	456
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	380	420	420	420
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11m carbon, 6Fattie/29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
REAR SHOCK	Custom Öhlins STX, Single-Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	Öhlins RXF36, 6Fattie/29, Twin-Tube design, air spring w/ adjustable 3rd chamber, adjustable high- & low-speed compression, adjustable rebound, 15x110mm thru-axle, 51mm offset, 150mm of travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 31.8mm
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on
FRONT BRAKE	SRAM Code RSC, hydraulic disc, 200mm
REAR BRAKE	SRAM Code RSC, hydraulic disc, 200mm
REAR DERAILLEUR	SRAM XX1, 11-speed
SHIFT LEVERS	SRAM XX1, 11-speed
CASSETTE	SRAM XG1199, XD, 11-speed, 10-42t
CHAIN	SRAM XX1, 11-speed w/ PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	Forged steel, 32T
RIMS	Roval Traverse 38 SL Fattie 650b, hookless carbon, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54T engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
REAR TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12-position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm of travel
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist
BATTERY	Turbo M1-504, integrated Trail Display, ANT+/Bluetooth® module, 504Wh, Mission Control App connectivity
CHARGER	Custom charger, 42V4A with Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95218-0002	LEVO FSR MEN SW CARBON 6FATTIE	CARB/HYP	S
95218-0003			M
95218-0004			L
95218-0005			XL

MEN'S TURBO LEVO FSR EXPERT CARBON 6FATTIE/29



RKTRED/CARB



CARB/FLKSIL

Often times, we forget the true essence of why we ride—to enjoy ourselves. And while many of the ear-to-ear grins come from the exploration aspect of riding, what do you do when they slowly fade as you fall into the habit of riding the same routes, day in and day out? You grab a Turbo Levo FSR Expert Carbon 6Fattie/29, and experience the smile-inspiring power to ride more trails.

- The Turbo Levo FSR frame is constructed with a FACT 11m carbon fiber chassis and M5 Premium Aluminum rear end, making it not only lightweight but also quite stiff and responsive. The design includes our Trail 6Fattie Geometry that includes a low bottom bracket, roomy top tube, and short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-504 battery features an integrated Trail Display and ANT+/Bluetooth® module with Mission Control App connectivity. It also houses 504Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	554	581	611	644
BB Drop (mm)	18	18	18	18
BB Height (mm)	340	340	340	340
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	69	69	69	69
Seat Tube Angle - Effective (deg)	74.2	73.9	73.6	73.3
Head Tube Angle (deg)	66.1	66.1	66.1	66.1
Wheelbase (mm)	1157	1185	1215	1250
Standover Height (mm)	753	762	772	780
Head Tube Length (mm)	95	100	130	150
Stack (mm)	598	603	630	649
Reach (mm)	386	411	430	456
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	380	420	420	420
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.		
FRAME	FACT 11m carbon chassis / M5 Alloy rear triangle, 6Fattie/29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel		
REAR SHOCK	RockShox Monarch RT3, Rx Trail Tune, AUTOSAG, rebound and 3-position compression adjust, 197x48mm		
FORK	Öhlins RXF36, 6Fattie/29, Twin-Tube design, air spring w/ adjustable 3rd chamber, adjustable high- & low-speed compression, adjustable rebound, 15x110mm thru-axle, 51mm offset, 150mm of travel		
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise		
HANDLEBARS	Specialized, 7075-T6 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width		
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on		
FRONT BRAKE	SRAM Code R, hydraulic disc, 200mm		
REAR BRAKE	SRAM Code R, hydraulic disc, 200mm		
REAR DERAILLEUR	SRAM X01, 11-speed		
SHIFT LEVERS	SRAM X1, trigger, 11-speed		
CASSETTE	SRAM XG-1175, 11-speed, 10-42t		
CHAIN	KMC X11ET, 11-speed w/ Missing Link™		
CRANKSET	Custom alloy crankarms		
CHAINRINGS	Forged steel, 32T		
RIMS	Roval Traverse 38 SL Fattie 650b, hookless carbon, 38mm inner width, 24/28h, tubeless ready		
FRONT HUB	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h		
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h		
SPOKES	DT Swiss, stainless		
FRONT TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"		
REAR TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"		
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm		
SEATPOST	Command Post IRCc, 12-position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm of travel		
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor		
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist		
BATTERY	Turbo M1-504, integrated Trail Display, ANT+/Bluetooth® module, 504Wh, Mission Control App connectivity		
CHARGER	Custom charger, 42V4A with Rosenberger plug		
WIRING HARNESS	Custom Specialized wiring harness		

PART NO.	DESCRIPTION	COLOR	SIZE
95218-3102	LEVO FSR MEN EXPERT CARBON 6FATTIE	RKTRED/CARB	S
95218-3103			M
95218-3104			L
95218-3105			XL
95218-3002	LEVO FSR MEN EXPERT CARBON 6FATTIE	CARB/FLKSIL	S
95218-3003			M
95218-3004			L
95218-3005			XL

MEN'S TURBO LEVO FSR COMP CARBON 6FATTIE/29



CARB/ACDRED



CARB/CMLN

Fun. It’s one word that we often forget about in our daily lives, but always find out on the trail. A feeling that we’re constantly seeking ways to maximize. And this is what the Turbo Levo FSR Comp Carbon 6Fattie/29 is all about—exploring more trails, and simply having more fun.

- The Turbo Levo FSR frame is constructed with a FACT 11m carbon fiber chassis and M5 Premium Aluminum rear end, making it not only lightweight but also quite stiff and responsive. The design includes our Trail 6Fattie Geometry that includes a low bottom bracket, roomy top tube, and short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-504 battery features an integrated Trail Display and ANT+/Bluetooth® module with Mission Control App connectivity. It also houses 504Wh of trail-taming juice, and it’s neatly integrated into the down tube.

LEVO FSR MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	554	581	611	644
BB Drop (mm)	18	18	18	18
BB Height (mm)	340	340	340	340
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	69	69	69	69
Seat Tube Angle - Effective (deg)	74.2	73.9	73.6	73.3
Head Tube Angle (deg)	66.1	66.1	66.1	66.1
Wheelbase (mm)	1157	1185	1215	1250
Standover Height (mm)	753	762	772	780
Head Tube Length (mm)	95	100	130	150
Stack (mm)	598	603	630	649
Reach (mm)	386	411	430	456
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	380	420	420	420
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.		
FRAME	FACT 11m carbon chassis / M5 Alloy rear triangle, 6Fattie/29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel		
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm		
FORK	RockShox Revelation RC 6Fattie/29, 51mm offset, 34mm stanchions, 150mm of travel		
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise		
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width		
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on		
FRONT BRAKE	SRAM Guide RE, hydraulic disc, 200mm		
REAR BRAKE	SRAM Guide RE, hydraulic disc, 200mm		
REAR DERAILLEUR	SRAM GX, long cage, 11-speed		
SHIFT LEVERS	SRAM GX, one-click shift-lever		
CASSETTE	SRAM PG-1130, 11-speed, 11-42t		
CHAIN	KMC X11ET, 11-speed w/ Missing Link™		
CRANKSET	Custom alloy crankarms		
CHAINRINGS	Forged steel, 32T		
RIMS	Roval 650b, alloy construction, 38mm internal width, 24/28h		
FRONT HUB	Specialized alloy disc, sealed cartridge bearings, 15x110mm, torque caps, 24h		
REAR HUB	Specialized alloy disc, sealed cartridge bearings, 12x148mm, 10-/11-speed freehub, 28h		
SPOKES	DT Swiss, stainless		
FRONT TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"		
REAR TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"		
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm		
SEATPOST	Command Post IRcc, 12-position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm of travel		
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor		
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist		
BATTERY	Turbo M1-504, integrated Trail Display, ANT+/Bluetooth® module, 504Wh, Mission Control App connectivity		
CHARGER	Custom charger, 42V4A with Rosenberger plug		
WIRING HARNESS	Custom Specialized wiring harness		

PART NO.	DESCRIPTION	COLOR	SIZE
95218-5602	LEVO FSR MEN COMP CARBON 6FATTIE	CARB/ACDRED	S
95218-5603			M
95218-5604			L
95218-5605			XL
95218-5702	LEVO FSR MEN COMP CARBON 6FATTIE	CARB/CMLN	S
95218-5703			M
95218-5704			L
95218-5705			XL



MEN'S TURBO LEVO FSR COMP 6FATTIE/29



FLKSIL/BLK/HYP

If you're looking to explore some new trails, expand your weekly ride routes, and have some fun doing it, the Turbo Levo FSR Comp 6Fattie/29 has the perfect blend of trail performance and power to give you the ride of your life.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts, strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail 6Fattie Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-504 battery features an integrated Trail Display and ANT+/Bluetooth® module with Mission Control App connectivity. It also houses 504Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	554	581	611	644
BB Drop (mm)	18	18	18	18
BB Height (mm)	340	340	340	340
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	69	69	69	69
Seat Tube Angle - Effective (deg)	74.2	73.9	73.6	73.3
Head Tube Angle (deg)	66.1	66.1	66.1	66.1
Wheelbase (mm)	1157	1185	1215	1250
Standover Height (mm)	753	762	772	780
Head Tube Length (mm)	95	100	130	150
Stack (mm)	598	603	630	649
Reach (mm)	386	411	430	456
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	380	420	420	420
Crank Length (mm)	165	165	165	165



BLK



RKTRD/BLK

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, 6Fattie/29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RC 6Fattie/29, 51mm offset, 34mm stanchions, 150mm of travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on
FRONT BRAKE	SRAM Guide RE, hydraulic disc, 200mm
REAR BRAKE	SRAM Guide RE, hydraulic disc, 200mm
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, one-click shift-lever
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	KMC X11ET, 11-speed w/ Missing Link™
CRANKSET	Custom alloy crankarms
CHAINRINGS	Forged steel, 32T
RIMS	Roval 650b, alloy construction, 38mm internal width, 24/28h
FRONT HUB	Specialized alloy disc, sealed cartridge bearings, 15x110mm, torque caps, 24h
REAR HUB	Specialized alloy disc, sealed cartridge bearings, 12x148mm, 10-/11-speed freehub, 28h
SPOKES	DT Swiss, stainless
FRONT TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
REAR TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRCc, 12-position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm of travel
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist
BATTERY	Turbo M1-504, integrated Trail Display, ANT+/Bluetooth® module, 504Wh, Mission Control App connectivity
CHARGER	Custom charger, 42V4A with Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95218-5102	LEVO FSR MEN COMP 6FATTIE	FLKSIL/BLK/HYP	S
95218-5103			M
95218-5104			L
95218-5105			XL
95218-5002	LEVO FSR MEN COMP 6FATTIE	BLK	S
95218-5003			M
95218-5004			L
95218-5005			XL
95218-5202	LEVO FSR MEN COMP 6FATTIE	RKTRD/BLK	S
95218-5203			M
95218-5204			L
95218-5205			XL

MEN'S TURBO LEVO FSR 6FATTIE/29



BLK/CMLN



ICEBLU/RKTRED

The Turbo Levo FSR Comp 6Fattie/29 has the perfect blend of trail performance, proper handling, technology, and durability, delivering you the power to ride more trails in a package that won't leave you broke and hungry.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts, strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail 6Fattie Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-460 battery features an integrated Trail Display, ANT+/Bluetooth® module, and Mission Control App connectivity. It also houses 460Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	554	581	611	644
BB Drop (mm)	18	18	18	18
BB Height (mm)	340	340	340	340
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	69	69	69	69
Seat Tube Angle - Effective (deg)	74.2	73.9	73.6	73.3
Head Tube Angle (deg)	66.1	66.1	66.1	66.1
Wheelbase (mm)	1157	1185	1215	1250
Standover Height (mm)	753	762	772	780
Head Tube Length (mm)	95	100	130	150
Stack (mm)	598	603	630	649
Reach (mm)	386	411	430	456
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	350	350	400	400
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, 6Fattie/29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Reba RL 29, 51mm offset, 150mm of travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on
FRONT BRAKE	SRAM Level T, hydraulic disc, 4-Piston Caliper, 200mm
REAR BRAKE	SRAM Level T hydraulic disc, 2-Piston Caliper, 200mm
REAR DERAILLEUR	SRAM NX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, one-click shift-lever
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	KMC X11ES, 11-speed w/ Missing Link™
CRANKSET	Custom alloy crankarms
CHAINRINGS	Forged steel, 32T
BOTTOM BRACKET	Shimano, outboard cartridge bearings
RIMS	Roval 650b, alloy construction, 38mm internal width, 24/28h
FRONT HUB	Specialized alloy disc, sealed cartridge bearings, 15x110mm, torque caps, 24h
REAR HUB	Specialized alloy disc, sealed cartridge bearings, 12x148mm, 10-/11-speed freehub, 28h
SPOKES	DT Swiss, stainless
FRONT TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
REAR TIRE	Butcher, GRID casing, 2Bliss Ready, 650b x 2.8"
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist
BATTERY	Turbo M1-460, integrated Trail Display, ANT+/Bluetooth® module, 460Wh, Mission Control App connectivity
CHARGER	Custom charger, 42V4A with Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95218-7002	LEVO FSR MEN 6FATTIE	BLK/CMLN	S
95218-7003			M
95218-7004			L
95218-7005			XL
95218-7102	LEVO FSR MEN 6FATTIE	ICEBLU/RKTRED	S
95218-7103			M
95218-7104			L
95218-7105			XL

## MEN'S TURBO LEVO FSR SHORT TRAVEL COMP 29



MXORG/BLK



PLAT/BLK

The Turbo Levo FSR Short Travel Comp 29 takes all of the pedal-assist wonderment of the Levo FSR family and reduces the travel length for those that prefer fully harnessing the speed of 29-inch wheels over big hit capability.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts, strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail 6Fattie Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-504 battery features an integrated Trail Display and ANT+/Bluetooth® module with Mission Control App connectivity. It also houses 504Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN ST				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	552.6	577	612	647
BB Drop (mm)	28	28	28	28
BB Height (mm)	345	345	345	345
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	70.9	70.2	70.2	70.2
Seat Tube Angle - Effective (deg)	75.4	75	74.8	74.4
Head Tube Angle (deg)	67.4	67.4	67.4	67.4
Wheelbase (mm)	1146	1174	1204	1238
Standover Height (mm)	757	767	775	781
Head Tube Length (mm)	95	100	130	150
Stack (mm)	589	594	621	639
Reach (mm)	399	424	443	469
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	380	420	420	420
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, 6Fattie/29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and two-position compression adjust, 197x48mm
FORK	RockShox Revelation RC 29, 51mm offset, 34mm stanchions, 120mm of travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on
FRONT BRAKE	SRAM Guide RE, hydraulic disc, 200mm
REAR BRAKE	SRAM Guide RE, hydraulic disc, 200mm
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, one-click shift-lever
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	KMC X11ET, 11-speed w/ Missing Link™
CRANKSET	Custom alloy crankarms
CHAINRINGS	Forged steel, 32T
RIMS	Roval Traverse 29, hookless alloy, 29mm internal width, tubeless-ready, 24/28h
FRONT HUB	Specialized alloy disc, sealed cartridge bearings, 15x110mm, torque caps, 24h
REAR HUB	Specialized alloy disc, sealed cartridge bearings, 12x148mm, 10-/11-speed freehub, 28h
SPOKES	DT Swiss, stainless
FRONT TIRE	Purgatory GRID casing, 2Bliss Ready, 29x2.3"
REAR TIRE	Ground Control GRID casing, 2Bliss Ready, 29x2.3"
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12-position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm of travel
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist
BATTERY	Turbo M1-504, integrated Trail Display, ANT+/Bluetooth® module, 504Wh, Mission Control App connectivity
CHARGER	Custom charger, 42V4A with Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95218-6002	LEVO FSR MEN ST COMP 29	MXORG/BLK	S
95218-6003			M
95218-6004			L
95218-6005			XL
95218-6102	LEVO FSR MEN ST COMP 29	PLAT/BLK	S
95218-6103			M
95218-6104			L
95218-6105			XL



MEN'S TURBO LEVO FSR SHORT TRAVEL 29



BLK/GLDORG



HYP/BLK



NBLBLU/RKTRED

The Turbo Levo FSR Short Travel 29 neatly places cutting-edge technology at a price that's sure to raise eyebrows. We gave it a short travel, 120mm design that places a focus on fully harnessing the speed of 29-inch wheels rather than big hits, so you'll never feel like you're running too much bike.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts, strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail 6Fattie Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery is fully integrated in the down tube and the motor is secured by a forged brace mount.
- The custom Turbo 1.3 Rx Trail-tuned motor is built for the Levo and features a 15% power increase and a significant efficiency increase compared to the Turbo 1.2 motor. This successfully places it at the top of e-bike motor technology. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- The Turbo M1-460 battery features an integrated Trail Display, ANT+/Bluetooth® module, and Mission Control App connectivity. It also houses 460Wh of trail-taming juice, and it's neatly integrated into the down tube.

LEVO FSR MEN ST				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	396	435	468	520
Top Tube Length (Horizontal) (mm)	552.6	577	612	647
BB Drop (mm)	28	28	28	28
BB Height (mm)	345	345	345	345
Chainstay Length (mm)	459	459	459	459
Seat Tube Angle - Actual (deg)	70.9	70.2	70.2	70.2
Seat Tube Angle - Effective (deg)	75.4	75	74.8	74.4
Head Tube Angle (deg)	67.4	67.4	67.4	67.4
Wheelbase (mm)	1146	1174	1204	1238
Standover Height (mm)	757	767	775	781
Head Tube Length (mm)	95	100	130	150
Stack (mm)	589	594	621	639
Reach (mm)	399	424	443	469
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seatpost Length (mm)	350	350	400	400
Crank Length (mm)	165	165	165	165

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, 6Fattie/29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and two-position compression adjust, 197x48mm
FORK	RockShox Reba RL 29, 51mm offset, 120mm of travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm width
GRIPS	MTB Lock-on CIP Grip SM & MD Thin lock-on / LG & XL Thick MTB lock-on
FRONT BRAKE	SRAM Level T, hydraulic disc, 4-Piston Caliper, 200mm
REAR BRAKE	SRAM Level T hydraulic disc, 2-Piston Caliper, 200mm
REAR DERAILLEUR	SRAM NX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, one-click shift-lever
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	KMC X11ES, 11-speed w/ Missing Link™
CRANKSET	Custom alloy crankarms
CHAINRINGS	Forged steel, 32T
RIMS	Roval Traverse 29, hookless alloy, 29mm internal width, tubeless-ready, 24/28h
FRONT HUB	Specialized alloy disc, sealed cartridge bearings, 15x110mm, torque caps, 24h
REAR HUB	Specialized alloy disc, sealed cartridge bearings, 12x148mm, 10-/11-speed freehub, 28h
SPOKES	DT Swiss, stainless
FRONT TIRE	Purgatory GRID casing, 2Bliss Ready, 29x2.3"
REAR TIRE	Ground Control GRID casing, 2Bliss Ready, 29x2.3"
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTOR	Turbo 1.3, custom Rx Trail-tuned motor
UI/REMOTE	Trail Handlebar Remote, motor mode switch & walk-assist
BATTERY	Turbo M1-460, integrated Trail Display, ANT+/Bluetooth® module, 460Wh, Mission Control App connectivity
CHARGER	Custom charger, 42V4A with Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95218-8002	LEVO FSR MEN ST 29	BLK/GLDORG	S
95218-8003			M
95218-8004			L
95218-8005			XL
95218-8102	LEVO FSR MEN ST 29	HYP/BLK	S
95218-8103			M
95218-8104			L
95218-8105			XL
95218-8202	LEVO FSR MEN ST 29	NBLBLU/RKTRED	S
95218-8203			M
95218-8204			L
95218-8205			XL